

ABSTRACT

A mobile station apparatus is provided that performs receive processing efficiently and reduces unnecessary power consumption. In this mobile station apparatus, a  
5 signaling detector (71) detects a compressed mode gap period in an uplink channel, that is, a period in which no uplink signal is transmitted to a base station, and reports this period to a controller (72). If the period detected in the signaling detector (71) contains  
10 transmission timing of an ACK/NACK signal, the controller (72) controls an HS-PDSCH receive processor (40) to stop the receive processing of the packet data corresponding to the ACK/NACK signal.

(12)特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関  
国際事務局(43) 国際公開日  
2005 年 2 月 17 日 (17.02.2005)

PCT


(10) 国際公開番号  
WO 2005/015780 A1

- (51) 国際特許分類: H04B 7/26 (72) 発明者; および  
(21) 国際出願番号: PCT/JP2004/011371 (75) 発明者/出願人 (米国についてののみ): 開 登志晃 (HI-RAKI, Toshiaki). 篠井 健一郎 (SHINOI, Kenichiro).  
(22) 国際出願日: 2004 年 8 月 6 日 (06.08.2004) (74) 代理人: 鷺田 公一 (WASHIDA, Kimihito); 〒2060034 東京都多摩市鶴牧 1 丁目 2 4-1 新都市センタービル 5 階 Tokyo (JP).  
(25) 国際出願の言語: 日本語  
(26) 国際公開の言語: 日本語 (81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.  
(30) 優先権データ: 特願2003-290699 2003 年 8 月 8 日 (08.08.2003) JP  
(71) 出願人 (米国を除く全ての指定国について): 松下電器産業株式会社 (MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.) [JP/JP]; 〒5718501 大阪府門真市大字門真 1 0 0 6 番地 Osaka (JP).

[続葉有]

(54) Title: MOBILE STATION APPARATUS AND RECEIVING METHOD

(54) 発明の名称: 移動局装置および受信方法



40...HS-PDSCH RECEPTION PROCESSING PART  
401...DESPREADING PART  
402...DEMODULATING PART  
403...DECODING PART  
404...ERROR DETECTING PART  
A...PACKET DATA  
50...HS-SCCH RECEPTION PROCESSING PART  
20...DUPLEXER  
30...RECEPTION PART  
501...DESPREADING PART  
502...DEMODULATING PART

503...DECODING PART  
504...DECIDING PART  
60...CPICH DESPREADING PART  
61...SIR DETERMINING PART  
62...CQI SELECTING PART  
70...DPCH DESPREADING PART  
71...SIGNALING DETECTING PART  
72...CONTROL PART  
80...TRANSMISSION PART

(57) Abstract: A mobile station apparatus capable of performing an efficient reception processing to suppress unnecessary power consumption. In this mobile station apparatus, a signaling detecting part (71) detects, from a signaling included in a DPCH as despread, a cap zone of a upstream compressed mode, that is, a zone in which no upstream signal is transmitted to any base stations, and notifies a control part (72) of the zone. If the transmission timings of ACK/NACK signals are included in the zone detected by the signaling detecting part (71), then the control part (72) causes an HS-PDSCH reception processing part (40) to stop the reception processings of the data packets corresponding to the ACK/NACK signals.

[続葉有]